



FLAMEXX SERIES VE PAINT ADDITIVE

Description VE paint additive is a water-soluble additive for paints and coatings.

Applications Mix Flamexx VE to acrylic paints and coatings.

Benefits and Features VE additive for paint transforms standard acrylic-based paints into a Class A fire resistant coating. Does not affect the paint manufacturer's application rate with 2 coats.

Typical Properties	Appearance	Clear Liquid
	PH	6.8 – 7.4
	Thermal Decomposition after dry	160 C

Usage Level Add one 8-oz. container of Flamexx VE to 1 gallon of latex paint.

Shipping Information Non-hazardous material per DOT
Available in 55 gallon drums, 5 gallon pails, or case/12 – 8 oz. bottle

Responsible Care Turning Star, Inc. is committed to the safety and well-being of our customers, employees and the community. Refer to the material safety data sheet for specific safety, handling, and toxicity information.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Turning Star, Inc. It is the responsibility of the users to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patents.